

DESIGN AND CONTROL OF DIVIDING-WALL COLUMN FOR TERT-BUTANOL DEHYDRATION SYSTEM VIA HETEROGENEOUS AZEOTROPIC DISTILLATION

ESCUELA SUPERIOR POLITÉCNICA DE CHIMBORAZO

RICHARD CARLOS ROJAS QUINTERO

Email: richard_r9731@yahoo.com

Background:

The production of tert-Butanol is used in great demand in chemical and pharmaceutical products, which is generally obtained by methods such as hydration or hydrolysis, being a product of great demand in the market in anhydrous tert-butanol, however the main difficulty that arises is the formation of a homogeneous azeotrope between t-butanol and water at atmospheric pressure. Failing to separate into pure components through ordinary distillation, azeotropic distillation being an effective method, a popular method but with a lot of energy expenditure. The tert-Butanol dehydration process using a dividing wall column process, through heterogeneous azeotropic distillation is a new technology in the development of the simulation, trying to reduce excessive energy consumption using dividing wall columns (A-DWC) for heterogeneous azeotropes.

Description of the flowsheet

The process of obtaining tert-Butanol begins with an equimolar mixture of t-butanol and water at a temperature of 298.15 K with an atmospheric pressure of 101 325 Pa, it should be noted that the entire process was carried out in SI units, in the first column (CC-1) that functions as a pre-concentrator column, in addition to an azeotropic distillation column (CC-2), in which the flow diagram generates a control loop, in which it was necessary to implement the Recycle Loops tool, so that you can run the flow diagram, in column three (CC-3) that acts as a rectifier, the energy of the first two columns is used without having a reboiler duty, achieving the reduction of energy consumption, At the end of the cycle at the head of the (CC-3) a Condenser Duty must be implemented with which it is taken to a decanter for the separation of two liquid phases, in this case it is necessary to add the drag component that is the cyclohexane, which achieves the formation of a desirable ternary azeotrope, in the decanter it is intended for the separation of an aqueous phase that is fed to (CC-1) and an organic phase that is connected to (CC-3) for rectification, it should be noted that The organic phase is the one with the highest

